IRONER TFI 6032



STANDARD FEATURES & BENEFITS

- · Ergonomic cylinder heated ironer
- \cdot Gas or electric heating
- · Extended heat transfer path
- · Large surface contact with linen
- · Roll standard with chrome surface coating for better thermal conduction and highly resistant to corrosion, even after periods of inactivity
- · Finger protection panel and emergency button for more safety
- \cdot Easy to use electronic control with pre-set ironing programmes
- · Indication of ironing temperature and speed
- · Frequency controlled motor
- $\cdot \ \text{Reverse mode possible} \\$
- \cdot Space-saving wall model with front return of the linen
- · Overheating check system with 2 temperature sensors
- \cdot Premix burner for more power and efficient ironing

OPTIONS

- · Longitudinal fold
- · 3 temperature sensors and partial LED lights
- · 3 folding sensors at feeding point instead of 1
- · Transport wheels



IRONER

TFI 6032

MODEL	UNIT	TFI 6032
Roll diameter	mm	600
Working width	mm	3200
Roll speed	m/min	3,5-12
	tic folding kg/h	110-130
	rik folding kg/h	180-200
HEATING		
Electric	1347	67.4
Electric heating power *	kW	67,4
Evaporation	l/h	80
Electric consumption Gas	kW/h	50
Gas power	kW	81,9
		60
	rik folding I ^{/h} tic folding I/h	100
Gas connection Ø	DN	20 (¾")
Gas pressure	mbar	20 (74)
Gas consumption	m³/h	8
VOLTAGE/ELECTRIC CONNECTION		·
Electric		
	3ph 50Hz	200/220/230/240/380/400/415 V
Gas	3ph 60Hz	200/208/220/240/380/415 V
das	1ph 50Hz	200/208/220/230/240 V
	1ph 60Hz	200/208/220/240 V
MOTOR		
Roll motor	kW	0,75
Fan motor	kW	1,1
EXHAUST		
Exhaust connection Ø	mm	125
Airflow		
Electric	m³/h m³/h	1125 1125
Gas		1123
DIMENSIONS (WxDxH)		
Standard	mm	4160x1360x1610
Packed	mm	4260x1510x1775
WEIGHT		
Net	kg	1940
Gross	kg	2160
SOUND LEVEL		
	db(A)	< 65,6

^{*} Output calculated at 380V/IIIphase

