


WASHER EXTRACTORS

TWE 10 · 15 · 18



STANDARD FEATURES & BENEFITS

- Freestanding, high spin washer
- Compact & modern space-saving design
- Large loading and unloading doors with up to 180° opening angle for easy access
- Choice of liquid and powder detergent in 5 compartment frontal dispenser
- Standard equipped for automatic soap dosing
- Drum and tub, as well as front and top panel made of robust and durable high quality stainless steel AISI 304
- Ceramic coated shaft for longer life due to less friction on sealing surfaces
- Highly flexible and freely programmable control with advanced 7" colour display for easy operation and perfect management of your laundry business
- USB connection for quick data transfer and data editing on simple .csv format
- On screen photographic illustrated troubleshooting guide
- Clear status light indication for easy and quick visual management
- Large 3" drain valve for fast evacuation and shorter cycles
- Accelerometer for perfect balancing
- Water inlet hoses
- Steam inlet hose

OPTIONS

- Dual heating (electric & steam) selectable through the control
- Stainless steel side panels
- Stainless steel back panel
- 3rd inlet valve for soft water
- High flow inlet valves for faster filling
- Pneumatic inlet valves for faster filling
- Pneumatic steam valve
- Chemical hold signal
- Integrated plinth to increase loading height and ensure ergonomic operation and fit linen carts

HENSON

LAUNDRY

WASHER EXTRACTORS

TWE 10 · 15 · 18

MODEL	UNIT	TWE 10	TWE 15	TWE 18
Dry load	kg	10	15	18
Performance	kg/h	15	22,5	27
Cycle time	min	30-45	30-45	30-45
DRUM				
Drum diameter	mm	630	630	630
Drum depth	mm	330	490	580
Drum volume	l	103	153	181
Wash speed	rpm	43	43	43
Extraction speed	rpm	1012	1012	1012
G-force		360	360	360
DOOR				
Door opening Ø	mm	455	455	455
HEATING				
Electric	kW	9	15	18
Steam	bar	4-6	4-6	4-6
ELECTRIC				
Electric consumption*	kWh	2,34	3,10	3,66
Motor	kW	1,5	2,2	3
STEAM				
Steam valve connection Ø	DN-BSP	15-½"	15-½"	15-½"
Steam pressure	kPa	400-600	400-600	400-600
Steam consumption	kg/cycle	5	7,5	9
AIR				
Air connection Ø	mm	optional / 8	optional / 8	optional / 8
WATER				
Inlet valve connection Ø	DN-BSP	2 x 20-¾"	2 x 20-¾"	2 x 20-¾"
Water inlet (detergent) Ø	DN-BSP	-	-	-
Water pressure	kPa	200-400	200-400	200-400
Water flow	l/min	60	60	140
Water consumption*	cold	l/cycle	39	58
	hot	l/cycle	42	62
Drain valve connection Ø (outer)	mm	76	76	76
Drain flow	l/min	230	230	230
PROGRAMMABLE CONTROL				
16 default programmes (max. 99)		Std	Std	Std
7" colour, high-resolution LCD		Std	Std	Std
DIMENSIONS (WxDxH)				
Standard	mm	880 x 976 x 1500	880 x 1136 x 1500	880 x 1226 x 1500
Standard with plinth	mm	880 x 976 x 1710	880 x 1136 x 1710	880 x 1226 x 1710
Packing	mm	930 x 1040 x 1550	930 x 1200 x 1550	930 x 1300 x 1550
Packing with plinth	mm	930 x 1040 x 1760	930 x 1200 x 1760	930 x 1300 x 1760
WEIGHT				
Net	kg	438	463	476
Net with plinth	kg	460	486	500
Gross	kg	460	488	504
Gross with plinth	kg	525	541	575
SOUND LEVEL				
	db(A)	55-65	55-65	55-65

* Consumption figures based on 'Eco 60°C' program (main wash, 2 rinses)