

WASHER EXTRACTORS

TWE 24 · 28 · 40



STANDARD FEATURES & BENEFITS

- Freestanding, high spin washer
- Compact & modern space-saving design
- Large loading and unloading doors with up to 180° opening angle for easy access
- Choice of liquid and powder detergent in 5 (TWE 24-28) or 6 (TWE 40) compartment frontal dispenser
- Standard equipped for automatic soap dosing
- Drum and tub, as well as front and top panel made of robust and durable high quality stainless steel AISI 304
- Ceramic coated shaft for longer life due to less friction on sealing surfaces
- Highly flexible and freely programmable control with advanced 7" colour display for easy operation and perfect management of your laundry business
- USB connection in the front for quick data transfer and data editing on simple .csv format
- On screen photographic illustrated troubleshooting guide
- Clear status light indication for easy and quick visual management
- Large 3" drain valve for fast evacuation and shorter cycles
- Accelerometer for perfect balancing
- High flow inlet valves for faster filling
- Water inlet hoses
- Steam inlet hose

OPTIONS

- Dual heating (electric & steam) selectable through the control
- Stainless steel side panels
- Stainless steel back panel
- 3rd inlet valve for soft water
- Pneumatic inlet valves for faster filling
- Pneumatic steam valve
- Second drain valve for water recovery
- Weighing cells to measure amount of linen and reduce the water, energy and detergent consumption accordingly
- Chemical hold signal

HENSON
LAUNDRY

WASHER EXTRACTORS

TWE 24 · 28 · 40

MODEL	UNIT	TWE 24	TWE 28	TWE 40
Dry load	kg	24	28	40
Performance	kg/h	36	42	60
Cycle time	min	30-45	30-45	30-45
DRUM				
Drum diameter	mm	700	700	900
Drum depth	mm	630	720	575
Drum volume	l	242	277	365
Wash speed	rpm	37	37	35
Extraction speed	rpm	961	961	847
G-force		360	360	360
DOOR				
Door opening Ø	mm	455	455	560
HEATING				
Electric	kW	21	24	30
Steam	bar	4-6	4-6	4-6
ELECTRIC				
Electric consumption*	kWh	4,90	5,60	8,93
Motor	kW	4	4	5,5
STEAM				
Steam valve connection Ø	DN-BSP	15-½"	15-½"	20-¾"
Steam pressure	kPa	400-600	400-600	400-600
Steam consumption	kg/cycle	12	14	20
AIR				
Air connection Ø	mm	optional / 8	optional / 8	optional / 8
WATER				
Inlet valve connection Ø	DN-BSP	2 x 20-¾"	2 x 20-¾"	2 x 20-¾"
Water inlet (detergent) Ø	DN-BSP	-	-	-
Water pressure	kPa	200-400	200-400	200-400
Water flow	l/min	140	140	140
Water consumption*	cold	l/cycle	78	89
	hot	l/cycle	86	99
Drain valve connection Ø (outer)	mm	76	76	76
Drain flow	l/min	230	230	230
PROGRAMMABLE CONTROL				
16 default programmes (max. 99)		Std	Std	Std
7" colour, high-resolution LCD		Std	Std	Std
DIMENSIONS (WxDxH)				
Standard	mm	975 x 1270 x 1565	975 x 1360 x 1565	1175 x 1405 x 1690
Standard with weighing option	mm	975 x 1270 x 1590	975 x 1360 x 1590	1175 x 1405 x 1715
Packing standard	mm	1020 x 1350 x 1620	1020 x 1440 x 1620	1240 x 1480 x 1740
Packing with weighing option	mm	1020 x 1350 x 1700	1020 x 1440 x 1700	1240 x 1480 x 1820
WEIGHT				
Net	kg	710	800	1025
Gross	kg	735	825	1060
SOUND LEVEL				
	db(A)	55-65	55-65	55-65

* Consumption figures based on 'Eco 60°C' program (main wash, 2 rinses)